

THE TEXACONE COMPANY  
4111 FORNEY ROAD  
MESQUITE, TX 75149

417

\*\*\*\*\* MATERIAL SAFETY DATA SHEET \*\*\*\*\*

**SECTION I. PRODUCT IDENTITY AND MANUFACTURER**

TRADE NAME: **JACK'S GREEN SLIME** MANUFACTURER'S NAME: **THE TEXACONE CO.**

CHEMICAL NAME AND SYNONYMS: Hydrocarbon grease with organic & inorganic additives.

CHEMICAL FAMILY: Polytetrafluoroethylene (TEFLON)

**SECTION II. HAZARDOUS INGREDIENTS**

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)
Pigments		N/A
Catalyst		N/A
Vehicle		N/A
Solvents		N/A
Additives		N/A
Others		N/A

ALLOYS AND METALLIC COATINGS	%	TLV (Units)
Base Metal		N/A
Alloys		N/A
Metallic Coatings		N/A
Filler Metal Plus Coating or Core Flux		N/A
Others		N/A

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES % TLV(Units)  
N/A

**SECTION III. PHYSICAL DATA**

BOILING POINT (°F): N/A	SPECIFIC GRAVITY (H <sub>2</sub> O=1): 1.11
VAPOR PRESSURE (mm Hg.): N/A	PERCENT, VOLATILE BY VOLUME (%): N/A
VAPOR DENSITY (AIR=1): N/A	EVAPORATION RATE: N/A
SOLUBILITY IN WATER: Insoluble	
APPEARANCE AND ODOR: Light green, buttery consistence, slightly mineral oil odor	

48

---

**SECTION IV. FIRE AND EXPLOSION HAZARD DATA**

---

FLAMMABLE LIMITS: N/A

EXTINGUISHING MEDIA: CO<sub>2</sub>, dry chemical or foam.

SPECIAL FIRE FIGHTING PROCEDURES: Use self contained breathing apparatus.  
Use water spray only to cool containers exposed to fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: May produce toxic fumes at temp.  
above 930°F.

---

**SECTION V. HEALTH HAZARD DATA**

---

EFFECTS OF OVEREXPOSURE: Primary hazard associated with grease in high pressure gun. If injected under the skin, necrosis could result. Possible irritation with repeated or prolonged contact.

EMERGENCY AND FIRST AID PROCEDURES -

EYES: Flush with water for at least 15 minutes.  
If irritation occurs consult physician.

SKIN: Wash with soap and water. If irritation occurs consult a physician.

INGESTION: Do not induce vomiting, seek medical advice.

---

**SECTION VI. REACTIVITY DATA**

---

STABILITY: Stable

INCOMPATIBILITY (Materials to avoid): Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion can yield CO, various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur.

---

**SECTION VII. SPILL OR LEAK PROCEDURES**

---

STEPS TO BE TAKEN IN CASE MATERIAL IS

RELEASED OR SPILLED: Pick up and place in container for disposal.

WASTE DISPOSAL METHOD: Dispose of in an approved landfill for lubricants. Burning is not recommended.

---

**SECTION VIII. SPECIAL PROTECTION INFORMATION**

---

RESPIRATORY PROTECTION: N/A VENTILATION: N/A

PROTECTIVE GLOVES: Grease resistant gloves. EYE PROTECTION: Goggles or safety glasses.

OTHER PROTECTIVE EQUIPMENT: N/A

---

**SECTION IX. SPECIAL PRECAUTIONS**

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in cool dry area and away from strong oxidizers.

OTHER PRECAUTIONS: Good personal hygiene and safe industrial practices should be observed.